Διάλεξη #13 - On Randomness

Εθνικό και Καποδιστριακό Πανεπιστήμιο Αθηνών

Εισαγωγή στην Ασφάλεια

Θανάσης Αυγερινός


```
int getRandomNumber()
{
    return 4; // chosen by fair dice roll.
    // guaranteed to be random.
}
```

FOUNDATIONS SOFTWARE CRYPTO SYSTEMS **HUMANS**

Huge thank you to <u>David Brumley</u> from Carnegie Mellon University for the guidance and content input while developing this class (some slides from Dan Boneh @ Stanford!)

Την προηγούμενη φορά

- About cryptography
- Terminology
- Traditional ciphers
- One-time pad



Ανακοινώσεις / Διευκρινίσεις

- Αναπλήρωση διάλεξης την Παρασκευή 2 Μαΐου, 11πμ Αίθουσα Β
- Είσαι σίγουρος ότι είναι ΟΚ να επιτρέπουμε το κλειδί "0" σε ΟΤΡ; Ή αντίστοιχα κλειδιά τα οποία έχουν συγκεκριμένα patterns;


Σήμερα

- Problems with just OTP
- Randomness and Pseudorandomness
- Probability and Math Reminders
- PseudoRandom Functions (PRFs)
- PseudoRandom Permutations (PRPs)



The "Bad News" Theorem

<u>Theorem</u>: Perfect secrecy requires |K| >= |M|




In practice, we usually shoot for <u>computational security</u>

More bad news


The OTP provides perfect secrecy ...

... but is that enough?


No Integrity



No Integrity




Our Goal: Secure Communication



Sub Goal 2: <u>Integrity</u>
Eve should not be able to alter *m*without detection


Detecting Modifications



Bob should be able to determine if M'=M

Ex: Eve should not be able to change Alice's message without detection (even if Eve doesn't know content of M)

Our Goal: Secure Communication




Sub Goal 3: <u>Authenticity</u>

Eve should not be able to forge messages as


Alice

Detecting Message Injection



Bob should be able to determine whether M was sent by Alice

Our Goal: Secure Communication



Secure Communication means: Secrecy, Integrity, and Authenticity

Still open: the pieces we need for secure communication

Everyone shares <u>same</u> secret k Only 1 party has a secret

	Symmetric Trust Model	Asymmetric Trust Model
Message Privacy	Private key encryptionStream CiphersBlock Ciphers	Asymmetric encryption (aka public-key encryption)
Message Authenticity and Integrity	Message Authentication Code (MAC)	Digital Signature Scheme

Principle 1: All algorithms are *public* (Kerckhoffs's Principle)

Principle 2: Security is determined only by key size

Principle 3: If you roll your own, it will be insecure



Crucial Ingredient: Randomness

- Explicit usage
 - Generate secret keys
 - Generate random "nonces" for encryption (more later on)
- Less obvious usage:
 - Generate passwords for new users
 - Shuffle cards in a poker game or votes in an election
 - Choose which work items to audit for correctness

Insecure Randomness: C rand()

• Many languages have a built-in "random" function


```
unsigned long int next = 1;
/* srand: set seed for rand() */
                                      What's the problem?
void srand(unsigned int seed) {
  next = seed;
/* rand: return pseudo-random integer on 0..32767 */
int rand(void) {
  next = next * 1103515245 + 12345;
  return (unsigned int) (next/65536) % 32768;
```

Insecure Randomness: C rand()

- Many languages have a built-in "random" function
- Given a few outputs, remaining values are predictable!

```
int getRandomNumber()
{
    return 4; // chosen by fair dice roll.
    // guaranteed to be random.
}
```

https://xkcd.com/221/



More Details

"How We Learned to Cheat at Online Poker: A Study in Software Security"

https://www.developer.com/tech/article.php/616221/How-We-Learned-to-Cheatat-Online-Poker-A-Study-in-Software-Security.htm

Sony PS3 vs. Randomness

27th Chaos Communication Congress

Console Hacking 2010

PS3 Epic Fail

Failuarila but


bushing, marcan, segher, sven

- 2010/2011: Hackers found/released private root key for PS3
- Key used to sign software
 - Load any software on PS3 and execute as "trusted"
 - i.e., Anyone can pretend to be Sony
- Flaw: Used same "random" number for every ECDSA signature

More Details

https://events.ccc.de/congress/2010/Fahrplan/attachments/ 1780 27c3 console hacking 2010.pdf

So... where does randomness come from?



http://dilbert.com/strip/2001-10-25

Obtaining "True" Randomness

- Gather entropy from unpredictable events
 - Ex: Linux "entropy pool" includes mouse & keyboard timing
 - Exposed via
 - /dev/random NEVER USE /dev/random its API is broken and wrong
 - /dev/urandom beware of subtle issues with file descriptors and child processes!!!
 - getrandom syscall always use this syscall when available
 - Randomness in the Operating System, or How To Keep Evil Children Out Of Your Pool and Other Random Facts Corrgan–Gibbs and Jana
- Physical random sources (do not use directly!)

More fun conversations at: https://lwn.net/Articles/889452/

- RDRAND instruction
- External devices






Quiz Question

Which of the following is likely to consistently provide secure randomness any time you query it?

- A. C's rand() function
- B. /dev/urandom
- C. Physical random sources
- D. /dev/random

Think this is an easy choice? Think again!



Probability 101

U: finite set (e.g. $U = \{0,1\}^n$)

Probability distribution P over U is a function P: $U \rightarrow [0,1]$ s.t.

$$\sum_{x \in U} P(x) = 1$$

 $A \subseteq U$ is called an event and $Pr[A] = \sum_{x \in A} P(x) \in [0,1]$

A random variable is a function $X:U \rightarrow V$.

X takes values in U and defines a distribution on V

Independence

Definition: events A and B are independent if Pr[A and B] = Pr[A] * Pr[B]Random variables X,Y taking values in V are independent if $\forall a,b \in V$: Pr[X=a and Y=b] = Pr[X=a] * Pr[Y=b]

Example:
$$U = \{0,1\}^2 = \{00, 01, 10, 11\}$$
 and $r \leftarrow U$

Define r.v. X and Y as: X = lsb(r), Y = msb(r)

$$Pr[X=0 \text{ and } Y=0] = Pr[r=00] = \frac{1}{4} = Pr[X=0] * Pr[Y=0]$$

The Birthday Paradox

In a room of 23 people, the probability that you share a birthday with one other person is greater than 50%.


The Birthday Paradox

Let $r_1, ..., r_n \in U$ be indep. identically distributed random vars.

Theorem: when $n = 1.2 \times |U|^{1/2}$ then $Pr[\exists i \neq j: r_i = r_j] \ge \frac{1}{2}$

Example: Let $U = \{0,1\}^{128}$

After sampling about 2^{64} random messages from U, some two sampled messages will likely be the same



Random Functions and Permutations

Thinking About Mathematical Functions

A function is just a mapping from inputs to outputs:

f_1				
X	$f_1(x)$			
1	4			
2	13			
3	12			
4	1			
5	7			

12				
X	$f_2(x)$			
1	1			
2	2			
3	3			
4	4			
5	5			

¹ 3				
X	$f_3(x)$			
1	12			
2	3			
3	7			
4	8			
5	10			

Which function is not random?

Thinking About Mathematical Functions

A function is just a mapping from inputs to outputs:

f	1	f	2	f	3	_
X	$f_1(x)$	X	$f_2(x)$	X	$f_3(x)$	
1	4	1	1	1	12	
2	13	2	2	2	3	
3	12	3	3	3	7	•
4	1	4	4	4	8	
5	7	5	5	5	10	


What is random is the way we *pick* a function

Participation Question

Consider all *functions* of the form F : X -> Y

How many possible choices of F are there?


- A. |X| * |Y|
- B. |X|!
- C. $|Y|^{|X|}$
- D. $|X|^{|Y|}$




Q: How many functions?

- $X = \{0, 1, 2\}$ (Domain)
- $Y = \{0, 1, 2, 3, 4, 5, 6, 7, 8, 9\}$ (Range)

 10^3 = 1000 possible functions







Encryption with Functions

- Alice chooses f: $\{0,1\}^b \rightarrow \{0,1\}^b$ at random from all possible functions from $\{0,1\}^b$ to $\{0,1\}^b$
- Alice gives Bob the inverse, f⁻¹
- Given message $m \in \{0,1\}^b$:
 - Alice sends f(m) to Bob
 - Bob decrypts using f⁻¹

Participation Question

Is this a correct cipher?

A. Yes

B. No


C. I'm not sure

Correctness

$$\forall m \in M, k \in K : D(k, E(k, m)) = m$$

Permutations: Definition

- f: X -> X
- A permutation:
 - Is a function that maps (->)
 every element of its domain to
 one element of its range
 - Ever element in the range is mapped to by exactly one element of the domain
- In math terms: f is one-to-one $\lor \forall x1, x2. f(x1) = f(x2) \Leftrightarrow x1 = x2$
- Colloquially, f is a shuffling of X



Participation Question


Consider all *permutations* of the form F : X -> X

How many possible choices of F are there?

B.
$$|X|^2$$

C.
$$|X|! \cong (|x|/e)^{|X|}$$

D.
$$|X|^{|X|}$$



Better Encryption Scheme?

- Alice chooses f: $\{0,1\}^b \rightarrow \{0,1\}^b$ at random from all possible *permutations* from $\{0,1\}^b$ to $\{0,1\}^b$
- Alice gives Bob the inverse, f⁻¹
- Given message $m \in \{0,1\}^b$:
 - Alice sends f(m) to Bob
 - Bob decrypts using f⁻¹

Participation Question

Is this a correct cipher?

- A. Yes
- B. No
- C. I'm not sure

Good cipher?

Better Encryption Scheme?

- Alice chooses f: {0,1}^b -> {0,1}^b at random from all possible *permutations* from {0,1}^b to {0,1}^b
- Alice gives Bob the inverse, f⁻¹
- Given message $m \in \{0,1\}^b$:
 - Alice sends f(m) to Bob
 - Bob decrypts using f⁻¹

No! Writing down f requires 2^b entries, each of which is b bits □ b*2^b bits in the "key" >> Messages are only b bits. We'd be much better off just choosing a one-time pad

Did we bypass "bad news" theorem?



Computational security

The system can be *practically* (not perfectly) indecipherable

- Security is only preserved against efficient adversaries running in polynomial time and space, with access to randomness
- Adversaries can succeed with a very small probability (small enough that it is essentially impossible)
 - Ex: Probability of guessing a large randomly chosen value

"A scheme is secure if every Probabilistic Polynomial Time (PPT) adversary succeeds in breaking the scheme with only negligible probability"

Ευχαριστώ και καλή μέρα εύχομαι!

Keep hacking!